



OROMECCANICA COMMERCIALE SRL

v. G. Ferraris 260-264 52100 Arezzo Italy
Tel. +39.0575.383151 Fax +39.0575.383152
E-mail oromeccanica@oromeccanica.com

SHEAR WITH FIXED EQUIPMENT Ø 120 mm



A very stout machine, constructed to cut plates in strips of predetermined sizes. The bed plate out of metallic carpentry, contains the motoring over mechanism, consisting out of a motor, a reducer and the gears. The tower, as shears-holder, is interchangeable, in order to allow a wide possibility of combinations and it can be equipped with a device, to push the plate against the shears, in order to facilitate the grip. The plate extractors are made out of hardened steel and guided from rolling pressers with adjustable springs. On request, we can assemble a winding and unwinding reel.

HEIGHT 1210 mm WIDTH 560 mm LENGTH 850 mm

MAX. THICKNESS TO BE SHEARED 2,30 mm

DIAMETER SHEARS 120 mm

CUT PORT 120 mm (ON REQUEST UNTIL 200 mm)

CUT SPEED Mt. 5,2 / 1'

POWER 2.2 Kw

FEEDING 220 - 380 Volt 50-60 Hz

WEIGHT 260 Kg WEIGHT WITH PACKING 380 Kg

SIZES OF THE PACKING 1010x710xh1460

CESOIA A PACCO Ø 120 mm

Macchina molto robusta costruita per il taglio di lastre in più nastri a misura prefissata.

La base in carpenteria metallica contiene il meccanismo di trascinamento formato da motore, riduttore e ingranaggi.

Il castello porta cesoie è intercambiabile onde permettere una vasta possibilità di combinazioni e può essere attrezzato con un dispositivo per spingere la lastra contro le cesoie in modo da facilitarne la presa.

Gli estrattori della lastra sono in acciaio temperato e guidati da pressori a rulli con molle registrabili. A richiesta possono essere montati aspo avvolgitore e devolgitore.

ALTEZZA 1210 mm. LARGHEZZA 560 mm. LUNGHEZZA 850 mm.

MAX SPESSORE CESOIABILE 2,30 mm.

DIAMETRO CESOIE 120 mm.

LUCE DI TAGLIO 120 mm. (A RICHIESTA FINO A 200 mm)

VELOCITA' DI TAGLIO Mt. 5,2 / 1'

POTENZA 2.2 kW.

ALIMENTAZIONE 220 - 380 Volt. 50 - 60 Hz.

PESO 260 Kg. PESO CON IMBALLO 380 Kg.

SIZES OF THE PACKING 1010x710xh1460

